

# Index

- 1D imaging, 72–73, 75, 86
- 2D imaging, 72–75, 86
- 2D optical correlators, 134
- 3D JTC, 135, 138
- 3D hybrid correlation, 144
- 3D imaging, 72–74, 86
- 4-f correlator, 134
  
- A/D converter, 99
- ALU, 97
- analog-to-digital conversion, 97
- arithmetic logic unit, 97
- ATR performance, 121–122, 124–125
- automated target recognition (ATR), 183, 185
  
- back-propagation network, 189
- bandwidth, 160
- bank of single nonlinear filters, 223
- beam steering, 86–88
- Bhattacharya distance, 40
- bottleneck, 92, 184
  
- capture phenomenon, 190
- Chebyshev's inequality, 168
- Chernoff distance, 40
- chi-square random variable, 181
- clutter rejector, 1, 3, 19, 24–25
- CMOS, 91, 184
- coherent detection, 82
- complex-conjugate, 147
- composite filter, 208, 212
- composite nonlinear filters, 212, 218
- computational functionality, 92
- computer-assisted diagnosis, 198
- computer-generated hologram (CGH), 61, 142
- controller chip, 104
- controlling instruction speed, 104
- convolution theorem, 137
  
- coordinate transformation, 146
- correlation, 113, 209
- correlation filter, 111–115, 120–122
- correlation peak, 126–127, 129
- correlators, 209
  
- data conversion, 184
- data transfer, 92
- decomposition, 115, 118–119
- decryption, 45, 48, 233–237, 239, 247
- degree of coherence, 151
- detection, 1–3, 9, 14–15, 25
- diagnosis, 201–202
- diffraction orders, 150
- digital holography, 45–46, 49
- digital phase-shifting interferometry, 52
- direct detection, 82
- discrimination capability, 210, 217
- distortion-invariant 3D correlator, 139
- distortion-invariant system, 208
- distortion-tolerant, 212
- double random phase encryption, 235
- double-phase encryption, 47
- $dSNR_k(0)/db$ , 166
- $dSNR_k^2(0)/db$ , 169–170
- dualband, 1, 13, 19, 21, 23–24
  
- Eckhorn's neuron model, 191
- eigenspace separation transform, 1, 8–9, 17, 19, 24
- eigentarget, 17
- encrypted data, 236, 239, 244–245, 248–249
- encryption, 45, 233, 235, 247
- encryption with digital holography, 49
- equal-correlation-peak synthetic-discriminant-function filter (ECP SDF), 212
- eye-safe wavelength, 77
  
- false detection, 188, 192
- fast Fourier transform (FFT), 56

- FFT algorithm, 61
- fill factor, 196
- filter bank, 212
- flood-illuminated imaging, 71
- forward-looking infrared, 1–3, 24
- four-step phase shifting, 56
- Fourier encryption, 50
- Fourier hologram, 49, 144
- Fourier lens, 136
- Fourier plane nonlinear filter, 160–162
- Fourier plane nonlinearity, 160
- Fourier transform, 55, 115, 137, 209
- Fourier-plane nonlinear filters, 212
- Fraunhofer diffraction pattern, 51
- Fresnel diffraction pattern, 59
- Fresnel encryption, 59
- Fresnel transform, 61
  
- gain, 79–80
- Gaussian noise, 170, 173
- Gaussian process, 164–165
- general processing capability, 96
- general purpose processing, 91, 93
- gesture recognition, 105
  
- high-speed grasping, 105
- high-speed image processing, 93
- high-speed parallel processing, 184
- high-speed product inspection, 93
- hologram, 49, 133, 146, 151
- hologram multiplexing, 46
- holographic memory, 234–236, 249
- holographic recording, 237
- holographic stereogram, 153
- hybrid 3D correlator, 135
- hybrid optoelectronic processors, 209
  
- I/O bottleneck, 93–94
- illumination-invariant system, 228
- image encryption, 47
- image preprocessor, 183
- image reconstruction, 134
- image security, 46
- image processing, 142
- inverse wavelet transform, 113
  
- Jacobi method, 6
- joint optimization, 116, 120–121
- joint transform correlator (JTC), 133–134, 144
- joint optimization, 122
- $k$ 'th-law equal-correlation-peak synthetic-discriminant-function filter (ECP SDF), 212, 214
- $k$ 'th-law Fourier plane nonlinear filters, 160, 162, 164, 166
- $k$ 'th-law MACE, 212, 214
- $k$ 'th-law nonlinear processor, 210
- Karhunen-Loeve (KL), 163
- Karhunen-Loeve series expansion (KL expansion), 163–164
  
- ladar, 71
- lidar, 71
- linear correlators, 210
- linear phase function, 147
- linear processors, 209
  
- MACE-SDF, 139
- MACH filter, 120, 122, 129
- MACH filters, 111, 121
- Mach-Zehnder interferometer, 50, 59
- massive parallelism, 96
- massively parallel processing, 93
- matched filter, 160, 162
- medical imaging, 198–199, 203–204
- microscope visual feedback, 106
- minimum average correlation energy (MACE), 208, 214
- misdiagnosis, 196–197
- missile guidance, 184
- multilayer perceptron, 1, 3, 11, 13–17, 19, 23, 25
  
- neural network, 183, 189
- noise, 194–195, 199
- noise bandwidth, 160
- noise robustness, 210
- nonlinear correlator, 210
- nonlinear ECP SDF filter, 220
- nonlinear filters, 160, 162, 181, 210
- nonlinear joint transform correlator, 162, 208
- nonlinear MACE filter, 220
- nonlinear processor, 208–209
- nonlinearity strength, 215
- nontraining targets, 215

- off-axis digital holography, 49
- on-axis digital holography, 49
- one-chip integration architecture, 93
- OPO, 83–84
- optical correlator, 134, 184–185
- optical encryption, 45–47, 49–50
- optical Fourier processor, 47
- optical pattern recognition, 133
- optical-to-digital converter, 185
- optimization, 124
- optimum correlation filter, 120
- optimum polarimetric selection, 37
- optimum threshold value, 189
- output detector, 185
  
- pattern recognition, 93, 120, 122, 134, 142, 209
- PCE parameter, 211
- PCE performance, 129
- PCE performance criterion, 126–127
- peak sharpness, 210, 217
- peak-to-correlation energy (PCE) parameter, 210
- peak-to-correlation energy (PCE) ratio, 126
- peak-to-sidelobe (PSR) ratio, 129
- phase conjugation, 49
- phase mask, 62
- phase retarders, 51
- phase-only filter (POF), 146
- phase-shifting digital holography, 45
- phase-shifting interferometry, 46, 53, 60
- photorefractive crystals, 49
- pixel parallel image processing, 104
- polarization diversity, 28
- polarization sensing, 75
- polarizations, 27
- polynomial correlation filter, 123
- power density of the stationary, 160
- power spectrum, 160–167, 173, 177, 181
- power spectrums, 160
- principal component analysis, 1, 5–8, 17, 19, 24
- processing speed, 203
- PSR, 129
- pulmonary data, 183
- pulse coupled neural network (PCNN), 185–190, 191–194, 199, 201, 203–204
- pulse coupled neuron (PCN), 187, 189–191, 194
- pulse-doublet, 85
- pulsing cycle, 192
  
- QR method, 6
- quadrature mirror filters (QMFs), 116–117, 119–124
  
- radar target recognition, 27
- radiological images, 196
- radiology, 203
- random distributions, 60
- random phase codes, 46
- random phase encoding, 46–47
- random phase key, 45
- random phase mask, 47, 235, 237–238, 248
- randomlike functions, 53
- range-gating, 81
- real background noise, 208
- received power, 76
- recognition, 1, 2, 13, 23
- recognition process, 226
- reconnaissance, 184
- reconstructed data, 246–248
- reconstructed images, 238, 241
- region of interest (ROI) locator, 193
- regions of interest, 185–186, 189, 192
- regions of no interest, 186–187, 189, 192, 199
- replication, 113, 115
- resolution, 78, 81
- retarder plates, 60
- road sign recognition system, 208
- robotic actuators, 97
- ROC curves, 17, 19, 21
  
- S<sup>3</sup>PE, 99
- SAR, 27
- scalability, 94, 102
- scale and illumination-invariant, 208
- scale-invariant, 214
- secure holographic memory, 235
- securing information, 46
- security, 45
- self-windowing, 105
- sensory processing elements (SPE), 97
- separable correlation filters, 125
- shift invariance, 134

- shift sensitivity, 123–124
- shift tolerance, 124
- signal-to-noise ratio (SNR), 77–81, 160–162, 166, 169–170
- simple and smart sensory processing element array, 99
- single-instruction stream multiple-data stream (SIMD), 99
- smoothing, 192, 199
- $SNR'_k(0)$ , 166
- $SNR_k$ , 163–166, 169–171, 173, 177, 181
- $SNR_k(0)$ , 165, 167
- $SNR_k^2(0)$ , 167
- solid state Raman laser, 84
- space-bandwidth product, 134
- space-to-time converter, 234, 239–241, 244
- spatial filter, 133, 146, 160
- spatial filtering techniques, 210
- spatial light modulator (SLM), 135, 184–185
- spatial spectrum, 135, 144
- spatial-temporal converters, 234, 243
- SPE-4k, 97
- speckle, 82
- spectral sensing, 74, 77–78
- stationary process, 163
- subband coefficients, 124
- subband decomposition, 113, 117–119, 122
- synthetic aperture radar, 27
- synthetic discriminant function (SDF), 139, 208
- target tracking, 134
- teleradiology, 198
- telescopic system, 155
- temporal frequency, 241–242, 245
- temporal frequency response, 241, 244
- three-dimensional correlators, 133
- three-level decomposition, 118–119
- thresholding, 188, 194
- time-to-space converter, 234, 245–246
- training process, 220
- training set, 215
- true target, 214
- truncated power spectrum, 163
- ultrafast data communication, 233–235
- ultrafast secure communication, 239
- ultrashort pulse, 240
- VanderLugt correlator, 134
- vibration sensing, 73–75, 81
- video sequence, 228
- vision chip, 91, 94, 96–97, 103
- vision chip algorithm, 104
- vision chip system, 104
- visual feedback, 93
- visual information processing, 92
- VLC, 144
- wavelet, 122
- wavelet coefficients, 115, 122–123
- wavelet transform, 113, 115
- wide sense stationary, 163